

Cisco® SPA 514G

Gigabit IP Phone

Advanced desk phone with speakerphone, 4 line keys,
Presence and Gigabit network interface



Enhance your business experience with the Cisco SPA 514G 4-Line IP phone with backlit display. It includes four line keys, VLAN-capable dual switched Gigabit Ethernet ports, Power over Ethernet (PoE) support, and a full-duplex speakerphone.

Make use of additional features, including HD Voice*, and intuitive menu options. For users who need to monitor presence, the phone can monitor up to 2 colleagues or up to 6 via expansion modules.

RingCentral provisions its devices before they ship, so you can start using your Cisco SPA 514G with plug-and-ring connectivity as soon as it arrives. The Cisco SPA 514G can even receive remote management, phone and user configuration, and software upgrades directly from RingCentral support.

*HD Voice is available for RingCentral customers in selecting plans

Cisco SPA 514G available with expansion modules

Turn your business phone into a high performance attendant console with this optimal solution for telephone attendants, receptionists, administrative assistants and secretaries.

- Monitors up to 32 additional users per expansion module
- Augments existing user interface
- Creates a high performance productivity enhancing solution with host phone
- Add or remove from host phone at any time



SPA 514G + 1 SPA500S Expansion Module



SPA 514G + 2 SPA500S Expansion Modules

Features and Specifications

Line Keys

- Up to 4 line keys for up to 4 simultaneous calls

Display

- Backlit LCD graphical display (128x64 pixels)

Feature Keys

- 4 illuminated call appearance line buttons with tricolor LEDs
- Dedicated hold key
- Dedicated voicemail key with 1-button access
- Dedicated menu key

- Dedicated lighted mute key
- Dedicated lighted headset key
- Dedicated lighted speakerphone key
- Dedicated lighted message waiting indicator
- 5-way navigational buttons
- 4 soft-key buttons
- Dedicated volume-control toggle

Call Control and Audio Features

- Call hold
- Music on hold
- Call waiting

- Caller ID name and number and outbound caller ID blocking
- Caller ID mapping for incoming calls
- Outbound caller ID blocking
- Call transfer – attended or blind
- Call conferencing – hosted (N-party) or local (3-party)
- Visual voice message waiting indicator (VMWI)
- Call back on busy
- Call blocking – anonymous and selective
- Do not disturb function
- Distinctive ringing based on calling and called number

Features and Specifications continued

Call Handling Features

- Distinctive incoming call treatment / call waiting
- Call timer
- Call transfer, hold
- Called, calling, connected party information
- Three-way conferencing
- One-touch speed dial, redial
- Call waiting
- Automatic off-hook call placement
- Do not disturb function

Network, Provisioning, and Maintenance

- Ethernet switch – 10/100/1000 PC switch port enables LAN connectivity to a co-located PC. Can designate separate VLANs (802.1Q) for the PC and Cisco IP phones, providing improved security and reliability of voice and data traffic.
- Web browser administration and configuration via integrated web server

Compliance

- FCC, CE, C-Tick, Wi-Fi, hearing aid compatible (HAC), Reduction of Hazardous Substances (RoHS), Bluetooth

Package Contents

- Cisco SPA 514G Desktop IP Phone
- Handset and cord
- RJ-45 Ethernet cable
- PA-100 power supply
- User guide
- Quick Tips reference card

Approvals

- FCC Part 15 (CFR 4) Class B
- ICES-003 Class B
- EN 55022 Class B
- CISPR 22 Class B
- CISPR 24
- EN 55024
- EN 50082-1
- EN 61000-3-2
- EN 61000-3-3

- EN 61000-6-1
- FCC Part 68 (CFR47) HAC

Safety

- UL 60950
- C-UL 60950
- EN 60950
- IEC 60950

Operating Conditions

- 32° to 113°F (0° to 45°C)
- Relative humidity: 5% to 95% noncondensing, operating, and nonoperating

Storage Temperature

- -13° to 176°F (-25° to 80°C)

Size

- 8.4 x 8.3 x 1.7 in
- 214 x 212 x 44 mm

Warranty

- 1 year