

SP-630 Touch Terminal



SP-630 Touch Terminal

- Intel Celeron N2807 Processor
- DDR3L memory 4GB
- Flexible modular design and dual display
- Convenient wall mount and wide tilt angle
- Splash and dust resistant front bezel, IP65



Biometric



I-Button



MSR

Partner Tech provides the right equipment for your business to expand and grow.

The SP-630 is a smart POS system designed to meet the needs of today's power hungry customer service applications. The fan-less Celeron N2807 processor and 4GB of RAM are combined in an elegant touch screen unit that features some of the most advanced and cost effective features found on any POS system.

Item	SP-630
CPU Type	Intel® Celeron processor N2807 (1M Cache, 1.58 GHz up to 2.16 GHz)
LCD	15" Active TFT color LCD LED, 350 nits, resolution 1024 x 768
Touch	5-wire Resistive touch
Memory	204 pin DDR3L SO-DIMM 4GB
Ethernet	IEEE 802.3 10/100/1000 BASE-T Gigabit Ethernet
Storage	Internal 2.5" type SATA HDD x 1
I/O Interface	3 * COM ports (COM1~3 at back I/O, powered with DC +5/+12V) 1 * DB-15 VGA port 1 * RJ11 port for 2 cash drawer(+24V) 1 * RJ-45 LAN port with activity and link LEDs 3 * USB 2.0, 1*USB 3.0 1 * DC +12V power adaptor connector
Expansion Options	1 * Mini PCI-e, Support Wireless Lan Module
Optional Peripherals	Three track Encryption Capable MSR Biometric Reader, Smart Card (EMV Ready) Reader, I-Button, RFID reader Customer facing display module (2 x 20 VFD) 11.6" 2nd monitor (Dual screen), 7" Customer Display
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 8.1 Industry pro Retail Linux (ubuntu)
Power Supply	AC100~240V/DC12V, 7.5A, 90 watt power adaptor
Dimensions (W-D-H)	36 x 24 x36.5 cm, 14.2" x 9.4" x14.5", 15° LCD tilt angle
Operating Temp	32°F ~ 104°F
Storage Temperature	-4°F ~ 140°F
Humidity	15%~80%
Certification	CE, FCC, VCCI, BSMI, CCC

*specifications are subject to change without prior notice

Flexible Modular Design and Dual Display Support



A wide variety of modules can be connected for different applications including RFID reader, MSR, fingerprint reader, Smart Card (EMV Ready) reader, and mini-PCI-E slot.

Convenient Wall Mount and Wide Tilt Angle



A compact form ensures that the SP-630 uses the minimum counter space.

Its wide tilt angle (0-90 degrees) and industry standard VESA mount offers highly flexible mounting options.

Splash and Dust Resistant Front Panel



Front Panel offers IP65 protection from water and dust. This rugged protection combines with Partner Tech's advanced engineering and high manufacturing standards.

Green Low Power Consumption



The Intel N2807 processor provides CPU performance whilst ensuring low power consumption, which reduces operating costs and protects the environment.