



# HP Value Receipt Printers

## Complete your retail solution

Both the HP Value Serial/USB Receipt Printer and the HP Value PUSB Receipt Printer are single-station thermal receipt printers designed for solid performance and reliability in retail environments. Choose an ubiquitous USB cable or legacy DB9 Serial cable to connect the HP Value Serial/USB Receipt Printer to your current systems. With the HP Value PUSB Receipt Printer, power up and connect using just one cable, a single powered USB. Simply connect your choice of printer to your platform, add paper, and you're ready to print.



### Customize your receipts.

Add a logo to your receipt or print special offers and coupons with integrated 2 MB Flash memory.

### Retail-ready design.

Place the compact printer where you need it with the assurance that the internal steel frame will withstand the everyday wear and tear of retail environments.

### Supported by HP.

Rest easy that your IT investment is supported by a three-year standard limited warranty. To extend your protection beyond the standard warranties, select optional HP Care Pack Services.<sup>1</sup>

<sup>1</sup> HP Care Pack Services are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit [hp.com/go/cpc](http://hp.com/go/cpc).

## HP Value Receipt Printers

### Specifications

<b>Print speed</b>	150mm/sec	
<b>Print method</b>	Direct thermal	
<b>Resolution</b>	203 DPI	
<b>Reliability</b>	MCBF Printlines 60 million MCBF Knife Cuts 2.3 million Printhead Life 242 km	
<b>Receipt columns</b>	44/56	
<b>Knife</b>	Self-sharpening ceramic rotary	
<b>Paper roll size</b>	3.1" x 3.55" (80 mm x 90 mm)	
<b>Paper thickness</b>	2.0–3.4 mil	
<b>Flash memory</b>	2 MB	
<b>RAM</b>	128 KB	
<b>Drivers</b>	Windows native, OPOS, JPOS	
<b>Cash drawers</b>	1 connector can drive 2 cash drawers with separately purchased splitter cable (default configuration is connection to 1 cash drawer)	
<b>Bar codes</b>	UPC-A, UPC-E, JAN8(EAN), JAN13 (EAN), Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, EAN 128, GS1 Databar, QR, and PDF-417 two dimensional codes.	
<b>Interface/Connection interface</b>	<b>HP Value PUSB Receipt Printer</b> Powered USB Interface (cable included)  24 V Cash Drawer support with RJ11 interface	<b>HP Value Serial/USB Receipt Printer</b> RS232 (9-Pin Female to 9-Pin Female NULL modem cable or standard USB 2.0 cable. Interface cables included)  24 V Cash Drawer support with RJ11 interface
<b>Operating voltage</b>	24 V	24 V
<b>Current</b>	Full load: 2.3 A w/active power management system, Idle current: 48mA, Idle power: 1.2W	
<b>Cable length</b>	<b>HP Value PUSB Receipt Printer</b> Powered USB cord: 9ft. (2.74m)(most models)	<b>HP Value Serial/USB Receipt Printer</b> Serial printer cable 9.8ft. (3m) USB cable: 6ft. (1.83m)
<b>Dimensions (W x D x H)</b>	5.65" x 7.27" x 5.27" (144mm x 185mm x 134mm)	
<b>Weight</b>	<b>HP Value PUSB Receipt Printer</b> 3lbs. 4oz. (1.47kg) (printer only) 5lbs (2.27 kg) (approximate with packaging and accessories)	<b>HP Value Serial/USB Receipt Printer</b> 3lbs. 4oz. (1.47kg) (printer only) 6 lbs. (2.72 kg) (approximate w/packaging & accessories)
<b>Color</b>	HP Carbonite	
<b>Temperature Range</b>	<i>Operating</i> 40° to 125° F (5 to 50° C) at 10% to 90% humidity (non-condensing at ambient)	<i>Non-operating</i> Transit range: 14°F to 122°F (-10°C to 50°C) 5% to 90% humidity  Storage range: -40°F to 140°F (-40°C to 60°C) 5% to 95% humidity
<b>Option Kit Contents</b>	<b>HP Value PUSB Receipt Printer</b> HP Value PUSB Receipt Printer, Starter paper roll, Powered USB cable.	<b>HP Value Serial/USB Receipt Printer</b> HP Value Serial/USB Receipt Printer, Starter paper roll, 24V external power supply, AC power cord, serial null printer cable, USB cable.

Learn more at  
[hp.com/go/POS](http://hp.com/go/POS)

